

TECHNICAL DATA SHEET

«DobroFarb»

Wood stain

MAIN CHARACTERISTICS

Thin-layer Lazure coating – is a highly effective protective and decorative wood product..

- finishing and deep protection of wood
- a transparent coating that enhances the natural appearance of the wood
- penetrates deeply into the surface
- the protective film does not crack or peel
- easy to apply

PURPOSE

For the protection and decorative finishing of exterior and interior wooden surfaces.

Recommended for wooden and other surfaces (fiberboard, chipboard) exposed to weather conditions and periodic contact with water.

Can be used for coating gazebos, garden furniture, doors, and other wooden items.

May also be used as a tinting base before applying alkyd and alkyd-urethane varnishes.

RELATED COMPONENTS

Solvent: «Miks color» Universal thinner
 «Miks color» Dearomatized thinner
 Xylene, solvent

TECHNICAL SPECIFICATIONS

Type	Modified alkyd
Density	(0,9) g/cm ³
Appearance of the dried coating	Uniform, smooth surface
Color	Pine, Mahogany, Oak, Teak, Chesnut, Rosewood, Walnut, Cherry, Macassar ebony, Colorless
Gloss	Satin

Consumption (surface coverage per one coat)	9-12 m ² /kg –
---	---------------------------

Drying time of each coat (at 20°C and 65% relative humidity), not more than	24 hours
---	----------

Drying time may be extended at lower temperatures and higher relative humidity.

Recommended Number of Coats	2-3
------------------------------------	-----

Intercoat Interval	The next coat should be applied after the previous layer has dried.
---------------------------	---

Packaging	0,7 kg; 2,2 kg;
------------------	-----------------

SURFACE PREPARATION

New surfaces:

Dry the wood thoroughly, clean it from dust, dirt, and wax, sand it, and remove all wood dust. Treat the surface with “Miks color” Universal Antiseptic (if necessary) and with “Miks color” Pore Filler VL-10 (to reduce the absorbency of the wood).

Repair of old coatings:

Remove loose and flaking particles of the old coating using a brush or sandpaper (grit 80–120 for rough sanding, 180–220 for finish sanding), then carefully remove all wood dust. Severely damaged coatings must be removed completely.

STAIN PREPARATION

Stir the stain thoroughly before use. The stain is supplied ready for application; if necessary, it may be thinned with a solvent in an amount of up to 5% of the stain mass.

APPLICATION

Application conditions:

Air temperature should be not lower than +5°C; relative air humidity should not exceed 80%.

Application:

Apply the stain to the prepared surface with a brush, roller, by dipping (for small parts), or with a spray gun, in a uniform, thin, continuous layer along the wood grain, avoiding overlaps of the stain layers.

Apply the next coat only after the previous one has dried.

Notes: For a high-quality finish, it is recommended to apply 2 coats of stain for interior use and 3 coats for surfaces exposed to weather conditions.

When repairing old coatings, choose a shade lighter than the previous one or mix the original color with a clear material.

The number of coats affects the final color—each additional coat increases color intensity.

Since the type of wood influences the final shade, it is recommended to perform a test application on a small area.

TOOL CLEANING

Remove any remaining stain with an organic solvent, then wash with water and a detergent.

STORAGE

Stain should be stored in a tightly closed factory container. Keep out of reach of children. Protect from moisture, heating devices, and direct sunlight

Warranty period of storage: 36 months from the date of production.

DISPOSAL

Do not spill liquid residues into drains, ponds or soil. Seal any remaining liquid product tightly and take it to an appropriate waste collection point.

Порожнє тару можна утилізувати як будівельне сміття.

SAFETY RECOMMENDATIONS

The stain is flammable. Keep away from fire!

Complies with the requirements of:

- Technical Regulation on limiting VOC emissions (A: subcategory 9(i), type (SB), Stage II, limit 500 g/L; the ready-to-use stain contains no more than 470 g/L).

- Technical Regulation on limiting the use of lead in paints, coatings, and raw materials (the stain does not contain toxic lead compounds).

During application and after completion of painting works, ensure thorough ventilation of the premises.

Use hand protection (rubber gloves).

Refer to the Material Safety Data Sheet (MSDS) and product label.

NOTES

A quality certificate is issued for each batch of the stain.

This information is based on the expertise of our specialists, obtained through laboratory research and practical experience. We do not accept responsibility for the use of our products outside our control and guarantee only the quality of the material itself. We reserve the right to make changes without prior notice to customers.

The quality system complies with the DSTU EN ISO 9001 standard.